

MANUFACTURER'S NAME AND ADDRESS

VMU Branch of Uralchem JSC in Voskresensk
Zavodskaya 1, Voskresensk,
Moscow Oblast, Russia, 140200
Tel.: +7 (496) 444-00-92
Fax: +7 (496) 444-02-73
E-mail: vmu@uralchem.com

Water-soluble NPK fertiliser with micronutrients

FINISHER 15-7-30+3MgO+TE, 12-6-36+2.5MgO+TE, 3-11-38+TE, 3-11-38+4MgO+TE

NPK fertilizer FINISHER are excellent water-soluble NPK fertilisers with high potassium content. Due to balanced nutrient ratio, it is recommended for use on all crops. When applying at late vegetation stages, Finisher increases plant resistance to drought, contributes to even ripening and better fruit bearing, improves taste, appearance and shelf life of yield, increases sugar content in sugar beet tubers. The product is made from ecologically clean raw materials and contains no sodium, chlorine and heavy metals. The fertiliser quickly dissolves in water. It is intended to use in greenhouses, open field and foliar application.

	15-7-30 +3MgO+TE	12-6-36 +2,5MgO+TE	3-11-38+TE	3-11-38 +4MgO+TE
Appearance	Crystal powder			
Total Nitrogen (N), %	15 ± 2	12 ± 2	min 3	min 3
- nitric N (N-NO ₃), %	8.7 ± 1	10.6 ± 1	min 0.2	min 3
- ammoniacal N (N-NH ₄), %	1.4 ± 1	1.4 ± 1	min 2.8	-
- ureic N (N-NH ₂), %	4.9 ± 1	-	-	-
Water-soluble Phosphates (P ₂ O ₅), %	7 ± 2	6 ± 2	11 ± 2	11 ± 2
Water-soluble Potassium K ₂ O, %	30 ± 2	36 ± 2	38 ± 2	38 ± 2
Water-soluble Magnesium MgO, %	3 ± 0.5	2.5 ± 0.5	-	4.0 ± 0.5
Moisture, %, max	0.5	0.5	0.5	0.5
Insoluble, %, max	0.1	0.1	0.1	0.1
MICROELEMENTS (* – IN CHELATED FORM), %, min.:				
- Boron (B)		0.02		
- Copper (Cu)*		0.01		
- Iron (Fe)*		0.1		
- Manganese (Mn)*		0.05		
- Molybdenum (Mo)		0.01		
- Zinc (Zn)*		0.01		
Free flowing, %	100	100	100	100

Packaging, transportation and storage

Packaging: 25 kg PE bags (palletized).

Transportation: by rail, road and water transport.

Storage: store in a dry and waterproof place, away from the exposure to moisture and direct sunlight.



The management system of the production site is certified to ISO 9001, ISO 14001 and ISO 45001